

BLS2 LINEAR - WALL DOWN AND UPLIGHT

2in Profile / Direct and Indirect Illumination / Selectable Output



SPECIFICATIONS

Output (per linear ft.)	Medium (725 lm/ft.) High (1000 lm/ft.) Very High (1200 lm/ft.) Custom (consult factory)
Light Distribution	50% Down / 50% Up 70% Down / 30% Up 100% Down
CCT / Color Temperature	3000K, 3500K, or 4000K
Color Rendering Index (CRI)	90+
Voltage	120-277V
Driver	0-10V (10%-100%)
Weight	Approx. 1.3 lb./ft. (may vary depending on additional options selected)
Environment	Suitable for Damp Location installations. Operating temperature range: -25°C to 50°C (-13°F to 122°F)
Materials	Aluminum housing with PC lens and endcaps
Finish Color	Black (BL) or White (WH) - powder coated

ORDERING GUIDE

Example: BLS2 - WDU - 4F - H - 50 - 30K - BL


PRODUCT CODE →

SERIES	MOUNTING	LENGTH	OUTPUT	LIGHT DISTRIBUTION	CCT	FINISH
BLS2	WDU					
BLS2 Blackjack Linear Slot	PDU Wall Down and Uplight	2F 2 ft. (nominal) 4F 4 ft. (nominal) 8F 8 ft. (nominal)	Standard M Medium H High V Very High Custom D### - U### (Select lm/ft)	70 70% Down / 30% Up 50 50% Down / 50% Up	30K 3000K 35K 3500K 40K 4000K	Standard BL Black WH White Special Order BZ Bronze SS Satin Silver SG Satin Gold Other CS Customer Specification
Consult factory for custom lengths.		Consult factory for custom outputs.				


OPTIONS →

MOUNTING DETAIL	SUSPENSION LENGTH	VOLTAGE	DRIVER	DRIVER LOCATION	OTHER
T Drop Ceiling/ T-Grid Adapter	72 72in (max.) (default) 300 300in (max.)	UNV Universal 120-277V (default)	ZT 0-10V (10% dimming) (default)	I Internal (default)	MH Mid-Run Power Harness Adapter
F Recessed / Full-Length Rails					
None is default. Leave blank for none.	Leave blank for default.	Leave blank for default.	Leave blank for default.	Leave blank for default.	None is default. Leave blank for none.

MOUNTING



DIMENSIONS (Standard)




OUTPUT (Standard)

LENGTH	LUMENS/WATTAGE		
	MEDIUM	HIGH	VERY HIGH
2 FT.	1450 LM 15W	2000 LM 20W	2400 LM 25W
	2900 LM 30W	4000 LM 40W	4800 LM 50W
8 FT.	5800 LM 60W	8000 LM 80W	9600 LM 100W

NOTE: For custom outputs, consult factory.


PHOTOMETRY




NOTE: Test protocol IES LM-79-80. Information for other options available upon request.

CONNECTOR ACCESSORIES (optional)


Internal Surfaced/Recessed - "CISR"





Internal Pendant/Wall - "CIPW"




L-shape - "CL"



T-shape - "CT"



X-shape - "CX"



ORDERING GUIDE - ACCESSORIES

SERIES

BLS2

BLS2
Blackjack Linear Slot

CONNECTOR TYPE



CISR - Internal (Surface/Recessed)
 CIPW - Internal (Pendant/Wall)
 CL - L-shape
 CT - T-shape
 CX - X shape

FINISH

Standard

BL Black

WH White

Special Order

BZ Bronze

SS Satin Silver

SG Satin Gold

Other

CS Customer Specification

MAX. CONNECTIONS:

2 ft. - 7 units

4 ft. - 7 units

8 ft. - 4 units

Example: BLS2 - CL - WH