

## SWIRL RGBW 16"

### Description

Custom light source options and high-tech controllers completely transform our 16", 23", and 32" Swirl fixtures. Go for brighter whites, a rainbow of color or hundreds of patterns of color synchronization, sequencing, advancing, rolling and more.

### Features

- Laser-cut steel construction with Satin Nickel finish
- 42" length adjustable stem kit includes three 12" stems and one 6" stem
- 144' wire length
- Fixture can accept up to four additional stem sections for a maximum overall fixture height of 51.1" (129.8 cm)
- Available in three sizes
- Hang straight swivel attaches to top of stem
- Damp location rated
- RGBW color controllable Swirl Pendant enables infinite color combinations and white light
- Lighting features can be manually controlled or use the many programmed color changing routines available pre-loaded in the controller

### Controls


- W1 - Wireless WIFI controller allows control of all color changing features through a cell phone and other wireless devices with downloadable app (IOS and Android OS). (Requires installer to remote mount the supplied driver near to the fixture canopy. Remote splice box not included.)
- W2 - Wireless hand-held controller provides a handheld remote controller (with wall-mounted holder) that allows control of all color changing features. (Requires installer to remote mount the supplied LED driver near to fixture canopy. Remote splice box not included.)
- H1 - Hardwired wall-mounted controller provides an easy to use touch control panel that operates all color changing features. Comes with wall mounted multi-function color control panel, 12' of five-conductor cable and terminal block. (Requires installer to remote mount the supplied LED driver near to control panel location. Remote splice box not included.)
- H2 - Hardwired DMX controller provides a cable connection to most DMX color changing controllers. Includes 12' of five-conductor cable and terminal block for connection to cable from remote mounted DMX controller. (Requires installer to remote mount the supplied LED driver near DMX controller. Remote splice box not included.)

### Specifications

- Color Rendering Index: 90 CRI
- LED Color Temperature: 3000K
- Input Voltage: 100-277VAC 50/60Hz
- Fixture Wattage: 55W
- Dimming: depends on Control Option
- Fixture weight: 10.42 lb. (4.74 kg)
- For recommended drivers, see <http://blackjacklighting.com>

### Options

- Consult ordering guide below for additional stems and Control options
- Special order fixtures are non-returnable; contact factory for Terms and Conditions



### ORDERING GUIDE

Family	Size/Type	Finish	Color Temp.	Control Options
SWL	- 16P	- SN	- RGB	- W1 W2 H1 H2

16P 16" Pendant      SN Satin Nickel      RGB - RGB(W)

Example: SWL-16P-SN-RGB-H2

### OPTIONAL ACCESSORIES

24" Additional Stem\*  
 Model No: 92001-24 (Satin Nickel)